

# Christie D4K2560/D4K3560



Amusement parks	Museums
Auditoriums	Planetariums
Casinos	Theaters
Classrooms	Virtual design centers



## The first high frame rate 4K DLP projectors Ultra-realistic 4K at 60Hz

Your audience will be raving about fantastic images and you'll know why. It's as real as it gets thanks to Christie's new and unique TruLife™ electronics, a quantum leap in video-image processing that is a breakthrough in high frame rate and high resolution video projection. The Christie® D4K2560 and D4K3560 offer ultra-realistic images and smoother video at 60Hz. Precise detail and vibrant life-like images won't fail to capture attention and immerse audiences in your content.

Now you have two 4K (4096 x 2160) choices for creating displays that require high brightness, ultra realism, superior color reproduction

and consistent long-life reliability. The Christie D4K2560 and the Christie D4K3560 are the only 4K resolution projectors built on superior 3-chip DLP® technology, giving you longer, more reliable lifetime performance and unequaled color reproduction with the widest color gamut. Furthermore, with 60Hz video processing motion blur and stuttered movement is significantly reduced, showcasing stunningly realistic visuals that are easy on the eyes.

Both projectors are designed to make it easy for you to put on a breath-taking show.

**CHRISTIE®**

		Christie D4K2560	Christie D4K3560
Image	brightness	<ul style="list-style-type: none"> <li>• 22,500 ANSI lumens (25,000 center lumens) - 3.0kW Lamp</li> <li>• 16,000 ANSI lumens (18,000 center lumens) - 3.0kW Lamp</li> <li>• 9000 ANSI lumens (10,000 center lumens) - 2.0 kW Lamp</li> </ul>	<ul style="list-style-type: none"> <li>• 32,500 ANSI lumens (35,000 center lumens) - 6.0kW Lamp</li> <li>• 27,000 ANSI lumens (29,000 center lumens) - 4.5kW Lamp</li> <li>• 18,000 ANSI lumens (19,500 center lumens) - 3.0kW Lamp</li> <li>• 12,000 ANSI lumens (13,000 center lumens) - 2.0kW Lamp</li> </ul>
	contrast	• 2000:1 (full on/off)	
Display	type	• 3-chip 1.38" DMD™	
	native resolution	• 4K (4096 x 2160)	
Lamp	type	• Xenon bubble	
	estimated life	<ul style="list-style-type: none"> <li>• 3.0kW lamp CDXL-30SD 1500 hrs</li> <li>• 3.0kW lamp CDXL-30 2500 hrs • 2.0kW lamp CDXL-20 3500 hrs</li> </ul>	<ul style="list-style-type: none"> <li>• 6.0kW lamp CDXL-60 750 hrs • 4.5kW lamp CDXL-45 900 hrs</li> </ul>
Input signals	standard	• 2 x Dual 3G HD-SDI input card • 2 x Twin DisplayPort input card	
	optional	• Dual Link DVI Input Card • Twin HDMI Input Card	
		Resolution	Connection
		• 4K (4096 x 2160)	• 4 x DisplayPort 1.1a
		• Quad HD (3840 x 2160)	• 2 x DisplayPort 1.1a
			• 4 x 3G HD-SDI
			• 4 x HD-SDI
			• 4 x DVI
			• 2 x DVI (Dual Link)
			Frame rate
			• 24-60Hz
			• 24-60Hz
			• 24-30Hz
			• 50-60Hz
			• 24-30Hz
			• 24-60Hz
			• 24-60Hz
			Format
			• 4:4:4 8-/10-bit • 4:2:2 8-/10-/12-bit
			• 4:4:4 8-/10-bit
			• 4:4:4 12-bit • 4:2:2 12-bit
			• 4:2:2 10-bit
			• 4:2:2 10-bit
			• RGB 8-bit
			• RGB 8-bit
Signal outputs	loop-out	• Dual 3G HD-SDI input card • Twin DisplayPort input card	
Control and networking		• RS-232 • Ethernet (10/100) RJ45 with ChristieNET™ connectivity • Detachable LCD control module	
Lenses	fixed	• 0.72:1* • 1.0:1**	
	zoom	• 1.13-1.31:1*** • 1.31-1.63:1 • 1.63-2.17:1 • 1.98-2.71:1 • 2.71-3.89:1 • 3.89-5.43:1 • 5.43:1-7.69:1***	
	offsets	• All lenses ±13% Vertical ±4% Horizontal except those noted below *No offset **1.0:1 fixed lens ±29% Vertical ±9% ***1.13-1.31:1 and 5.43:1-7.69:1 zoom lenses ±56% Vertical ±19%	
Accessories	standard	<ul style="list-style-type: none"> <li>• Detachable LCD control module • AC line cord for projector head</li> <li>• CDXL-30SD lamp</li> </ul>	<ul style="list-style-type: none"> <li>• Detached 7kW low-ripple switch mode lamp ballast (required to operate projector) • CDXL-60 lamp</li> </ul>
	optional	<ul style="list-style-type: none"> <li>• CDXL-20 lamp • CDXL-30 lamp</li> <li>• Heat extraction fan kit (required when operating projector) • Rack mount pedestal • Replacement air filter for light engine</li> <li>• Replacement air filter for liquid cooling radiator • Lamp adapter kit for CDXL-20 • Christie Twist™ 4K (limited to 30 frames per second)</li> </ul>	<ul style="list-style-type: none"> <li>• CDXL-20 lamp • CDXL-30 lamp • CDXL-45 lamp</li> </ul>
Lens mount	type	• Tool-free lens insertion system • Boresight adjustable • Motorized horizontal and vertical lens offset • Motorized zoom and focus adjustment	
Power requirements	projector head	<ul style="list-style-type: none"> <li>• Operating voltage: Single phase 200-240 VAC @ 50/60Hz</li> <li>• Operating current: 23A max @ 200V</li> </ul>	<ul style="list-style-type: none"> <li>• Operating current: 7A max @ 200V</li> </ul>
	ballast	• Integrated ballast and projector head	<ul style="list-style-type: none"> <li>• Type: Detached 7kW low-ripple switch mode lamp ballast</li> <li>• Operating voltage: 3-phase 200-230 VAC @ 50/60Hz</li> <li>• Operating current: 38A per phase max</li> <li>• Operating voltage: 3-phase 380-415 VAC @ 50/60Hz</li> <li>• Operating current: 26A per phase max</li> </ul>
Dimensions	size	• Projector head (LxWxH): 51.1 x 25.5 x 19.0" (1299 x 648 x 480mm) with lens cover	<ul style="list-style-type: none"> <li>• Projector head (LxWxH): 51.1 x 25.5 x 19" (1298 x 648 x 483mm)</li> <li>• Ballast (LxWxH): 21 x 18 x 21" (533 x 457 x 533mm)</li> </ul>
	shipping size	• Projector head (LxWxH): 60.4 x 36 x 28.5" (1535 x 914 x 724mm) with lens cover	<ul style="list-style-type: none"> <li>• Projector head (LxWxH): 60.4 x 36 x 28.5" (1535 x 914 x 724mm)</li> <li>• Ballast (LxWxH): 28 x 25 x 31.5" (710 x 635 x 800mm)</li> </ul>
	weight	• Projector head 273lbs (124kg)	• Projector head 251lbs (114kg) • Ballast 89lbs (40.5kg)
	shipping weight	• Projector head 344lbs (156kg)	• Projector head 322lbs (146kg) • Ballast 135lbs (62kg)
Operating environment		• Operating temperature: 50-95°F (10-35°C) • Humidity (non-condensing): 20-80%	
Regulatory		<ul style="list-style-type: none"> <li>• This product conforms to the following regulations related to product safety, environmental requirements and electromagnetic compatibility (EMC): • Directives: (EC) 2011/65/EU (RoHS) • 2012/19/EU (WEEE)</li> <li>• Regulations: (EC) No. 1907/2006 (REACH) • CAN/CSA C22.2 No. 60950-1 • UL 60950-1 • IEC 60950-1 • EN 60950-1 • FCC, Part 15, Subpart B, Class A • ICES/NMB003 (A) • EN55022/CISPR22 Class A • EN55024/CISPR24</li> <li>• The product is designed to comply to the rules and regulations required for the product to be sold in various regional markets, including: USA/Canada, EU, Norway, Australia/New Zealand, Kuwait, China, Korea, Japan, Mexico, Ukraine, Russia, South Africa, and Saudi Arabia</li> </ul>	
Limited warranty	projector	• Three years parts and labor (including light engine)	
	lamp	• Contact an authorized Christie representative for full details of our limited warranty	

#### Corporate offices

Christie Digital Systems USA, Inc  
USA – Cypress  
PH: 714 236 8610

Christie Digital Systems Canada Inc.  
Canada – Kitchener  
PH: 519 744 8005

#### EMEA offices

United Kingdom  
Branch & EMEA  
Head Office  
ViewPoint  
200 Ashville Way  
Wokingham  
Berkshire, U.K.  
RG41 2PL  
PH: +44 (0) 118 977 8000

Africa  
Branch Office  
PH: +27 (0)11 510 0094

Eastern Europe  
Representative Office  
PH: +36 (0)1 47 48 100

France  
Branch Office  
PH: +33 (0) 1 41 21 44 04

Germany  
Branch Office  
PH: +49 2161 664540

Middle East  
Branch Office  
PH: +971 (0) 4 320 6688

Spain  
Branch Office  
PH: +34 91 633 9990

Italy  
Independent Sales Consultant Office  
PH: +39 (0) 2 9902 1161

Russia  
Independent Sales Consultant Office  
PH: +7 (495) 930-8961



For the most current specification information, please visit [www.christieemea.com](http://www.christieemea.com)

Copyright 2014 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
CHR13541\_EN\_JAN14

**CHRISTIE**®