# Ca<sub>B</sub>



## **DLAseries DLA406**

Line Array System

#### **FEATURES**

- Special designed waveguide and horn, ensure accurate coverage angle and uniform changes
- Passive way, simple operation, save amplifiers
- Quick setup for hanging, stacking and supporting
- Applications: multifunction halls, lecture halls, auditoriums, churches, and small touring

#### 系统特征

- ●专门设计的波导管及号角:保证覆盖角度 精准,变化均匀
- ●内置分音:操作简单,节省功放及周边设备
- 多种组合使用方式:吊挂、堆码、支撑, 安装快捷、安全


### 适用范围


- ●多功能厅、报告厅、礼堂、教堂
- ●小型流动演出


**DLA406** is a small-sized, light weight, integrated line array speaker. It features low distortion mid-bass unit, high quality HF driver with special waveguide and horn, accurate coverage, uniform changes, two-point hanging system is simple and easy to install, can be used in a single, two or three pieces combination. Unit configuration: 4 x6" high efficiency neodymium midbass units, 2x1" exit throat 44mm voice coil neodymium HF drivers. The cabinet is made of multilayer composite plywood with wear-resistant polyurea paint.

DLA406是一款小型、集成式线性阵列音箱,具有体积小、重量轻等特点,应用低失真中低音单元,高品质高音驱动器配上专用波导管及号角。覆盖精确、变化均匀。两点吊挂系统简单易安装,可单只、两只、三只组合使用。单元配置:4只6"钕磁中低音单元,2只1"喉口44芯钕磁高音驱动器;箱体采用多层复合夹板,耐磨聚脲喷涂。

#### CONFIGURATION









RATED POWER SENSITIVITY MAXIMUM SPL IMPEDANCE DISPERSION(-6dB)

CROSSOVER FREQUENCIES
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

DLA406
80Hz-18kHz
75Hz-20kHz
4×6"(150mm)/1.5"voice coil LF
2×1"(25mm)/1.7"voice coil HF
320W RMS,1280W peak
99dB 1watt/1 metre
124 dB continuous,130 dB peak

8 ohms nominal Horizontal coverage: 100°

Vertical coverage: Varies, depending on array length and configuration

1.1kHz passive

2×Speakon NL4

435mm $\times 435$ mm $\times 540$ mm

14 kg/pc

17 kg/pc

